



## H1050 Wheel Loader

# SPECIFICATIONS



Specification	overall weight(kg)	10600
	L×W×H (mm)	7750×2540×3120
	rated bucket capacity(m <sup>3</sup> )	1.8
	Rated load(kg)	3000
	Maximum dump height (mm)	3200
	Bucket indicator	Yes
	Max. breakout force(KN)	138
Engine	Model	<b>Cummins 6BT5.9-C150</b>
	Type	In line, direct injection, four-stroke, liquid cooled
	Rated power (kw) (HP)	<b>110kw 150HP</b>
	Rated speed(r/min)	2300
Transmission system	Model of torque converter	YJ315X
	Type	Single stage,3 elements
	Gearbox model	YD13044159
	Gear shift	4 gears ahead,3 gear astern
Hydraulic system	Distribution of work valve	DF25.3
	Working pump	VHP2100/1010-xfl, CBGJ1032L,FC50
Steering system	Type	Articulated and hydraulic steering
	Max. turning angle	lift and right 36.5±1°
	Min turning radius(mm)	5862
Brake system	Brake type	Air-break brake
Tires	Standard tires	17.5-25



Distributed by - BME Sales  
 28 Old Pacific Highway, Yatala Qld 4207  
 TEL: 07 3807 4333  
[www.bmesales.com.au](http://www.bmesales.com.au)